

# Auto Scrubber

**FELLOW**   
SINCE 1987



CE

MADE IN TAIWAN

Type **CB-17 / CB-201 (CB-21)**  
**CB-17D / CB-201D (CB-21D)**

## ◆ FEATURE

1. Efficient cleaning. Scrub, wash & dry the floor in one pass.
2. With BLDC motors, it is high efficiency, maintenance free, long life, energy saving and environmental protection.
3. The microcomputer panel is easily maneuverable.
4. The body of the machine is polyethylene. It is heavy-duty and resistant to acids and alkalis.
5. The protruding cylindrical brush enables edge-close working and it has corner rollers.
6. The scrub brush skirt is designed to prevent slop the dirty water and splash foam.
7. Minimize noise levels to as low as 70dBa.
8. Independent motor; microcomputer controls continuously variable transmission (CVT).
9. It has two tanks and drains which are convenient to discharge waste and clean water.
10. The curved squeegee blade has corner rollers. With oil resistant squeegees, it sucks up water and dries the floor rapidly.
11. Battery LED indicator. When it is low voltage, it stops automatically to protect battery.
12. Warning light shines when the recovery tank is full, and then the machine will stop to protect vacuum motor automatically.
13. It has disk brush load and unload system. (Panel control)



The BLDC motor is high efficiency, maintenance-free, long life, save energy and Ecofriendly.



The microcomputer panel is very stable and easily maneuverable.

The nylon brushes and scrubbing pads can change by the type of the floor.



The scrub brush skirt is designed to prevent slop the dirty water and splash foam.



## ◆ SPECIFICATION

TYPE	CB-17	CB-17D	CB-201	CB-201D
Power source	Battery	Battery	Battery	Battery
Area performance	1,930 m <sup>2</sup> /hr	1,930 m <sup>2</sup> /hr	2,650 m <sup>2</sup> /hr	2,650 m <sup>2</sup> /hr
Run time	2 ~ 3 hours	2 ~ 3 hours	2 ~ 3 hours	2 ~ 3 hours
Cleaning path	430 mm	430 mm	530 mm	530 mm
Squeegee width	760 mm	760 mm	760 mm	760 mm
Disk brushes	17 inch × 1pc	17 inch × 1pc	20 inch × 1pc	20 inch × 1pc
Sound level	70 dBA	70 dBA	70 dBA	70 dBA
Disk brush rotations	220 rpm	220 rpm	220 rpm	220 rpm
Disk brush BLDC motor	800 W	800 W	800 W	800 W
Vacuum BLDC motor	500 W	500 W	500 W	500 W
Forward motor	-----	400 W	-----	400 W
Forward way	Semi-automatic	Automatic traction	Semi-automatic	Automatic traction
Forward speed	-----	0 ~ 5 km/hr	-----	0 ~ 5 km/hr
Brush pressure	28 kg	28 kg	30 kg	30 kg
Solution tank	42 L	42 L	42 L	42 L
Recovery tank	51 L	51 L	51 L	51 L
Battery	12V/100Ah × 2pcs	12V/100Ah × 2pcs	12V/100Ah × 2pcs	12V/100Ah × 2pcs
Charger	--- 24V/15A (DC output) ---		--- 24V/15A (DC output) ---	
Dimensions	--- L: 1,175 × W: 510 × H: 1,050 (mm) ---		--- L: 1,210 × W: 560 × H: 1,050 (mm) ---	
Weight	75 kg	80 kg	76 kg	81 kg
Weight(with batteries)	127 kg	132 kg	128 kg	133 kg

Specifications and details are subject to change without prior notice.

飛樂科技有限公司  
FELLOW TECHNOLOGY CO., LTD.

Telephone: +886 6 253 6611 Fax: +886 6 253 7786  
Website: www.fellowyc.com.tw E-mail: yc@fellowyc.com.tw

FELLOW KEEPS THE WORLD CLEAN