Vacuum Sweeper Walk Behind Self-propelled







🌣 Feature:



Just loosen three screws, you can turn down the main brush for trouble-shooting.



With the side brush, corner's can be swept efficiently.



Lightweight and durable hopper easy to be removed for convenient disposal of



The filters can be removed easily cleaning down the trapped dusts to ensure the perfect performance.



BLDC Motor-high efficiency, energy conservation. environmental protection, maintenance-free, and longer

Feature:

- 1.Corner can easy to sweep.
- 2.Chassis height 6 cm.
- 3.Remove dust from filter by electric shaker.
- 4. Save electricity.
- 5.Can be sweeping on floor.
- 6.Honda petrol engine (26-G, 36-G).

Forward Speed is variable from 0 to 4.5 km/h and most of the parts of the sweeper models 26-B, 26-G, 36-B, 36-G are interchangeable.

The FELLOW Designers consider the suggestions made by the users from all over the world to come to a better and improved product.



automatical operating system for dashboard, simple operation, and fast.

Application:

Factories, Warehouse, Parking Lots, Amusement and Recreational Area...



Specification

| Model | 26-B | 26-G | 36-B | 36-G |
|------------------------------------|--|-------------------------------------|---|--------------------------------------|
| Power | 12V/100AH x2 (Battery) (24V x 1 HP) | Petrol Engine (Honda GX-120) | 12V/100AH x 2 (Battery) (24V x 1 HP) | Petrol Engine (Honda GX-120) |
| Area Performance | 2,925 m²/hr (Max) | 2,900 m ² /hr (Max) | 4,100 m²/hr (Max) | 4,100 m ² /hr (Max) |
| Run Time | Up to 3 hrs | 24 hrs | Up to 3 hrs | 24 hrs |
| Sweeping Width | 660 mm (26 inch) | 660 mm (26 inch) | 920 mm (36 inch) | 920 mm (36 inch) |
| Sweeping Width(without side brush) | 500 mm | 500 mm | 700 mm | 700 mm |
| Main Brush | Ø265 x 500mm | Ø265 x 500mm | Ø265 x 700mm | Ø265 x 700mm |
| Side Brush | Ø400 mm | Ø400 mm | Ø570 mm | Ø570 mm |
| Batteries | 12V/100AH x 2 | 12V/4AH | 12AH/100AH | 12V/4AH |
| Hopper Capacity | 40 L | 40 L | 42 L | 42 L |
| Filter System | 4.5 m ² (2PCs of filter) | 4.5 m ² (2PCs of filter) | 6.75 m ² (3PCs of filter) | 6.75 m ² (3PCs of filter) |
| Chargers | 24V x 10A, Automatic | 24V x 4A, Automatic | 24V x 10A, Automatic | 24V x 4A, Automatic |
| Chassis Height | 60 mm | 60 mm | 60 mm | 60 mm |
| Dimensions | L:1080mm x W:580mm x H:910mm | L:1080mm x W:580mm x H:910mm | L:1160mm x W:770mm x H:970mm | L:1160mm x W:770mm x H:970mn |
| Weight | 82 Kg | 100 Kg | 102 Kg | 122 Kg |
| Weight (with batteries) | 130 Kg | 102 Kg | 150 Kg | 124 Kg |

In the interest of technical development we reserve the right to alter equipment without prior notice.

PROFESSIONAL MANUFACTURER

FELLOW Y.C. CO., LTD.

Taipei: No.5, LANE 33, Wufu Rd., Wugu Dist., New Taipei City, Taiwan Tel:+886-2-2291-5309 Fax:+886-2-2292-5134

Tainan: No. 39, Lane 146, Yansin St., Yongkang Dist., Tainan City, Taiwan Tel:+886-6-253-6611 Fax:+886-6-253-7786